CLAIMS:

5

10

15

1.

channels of said first plate; and

a first plate having flow channels defined at one side thereof, said flow channels of said first plate being orientated in a first direction, said

A waste energy recovery assembly, comprising:

first plate having a supply opening and an exhaust opening therein, said exhaust opening of said first plate positioned for communicating with said flow

a second plate having flow channels defined at one side of said second plate, said flow channels of said second plate being orientated in a second direction, said second plate having a supply opening and an exhaust opening therein, said supply opening of said second plate positioned for communicating with said flow channels of said second plate, said second plate being disposed in thermal communication with said first plate with said supply opening of said second plate aligning with said supply opening of said first plate and with said exhaust opening of said second plate aligning with said exhaust opening of said first plate.

- 2. The waste energy recovery assembly of Claim 1 wherein said flow channels in each of said first plate and said second plate are defined by etchings in said first plate and etchings in said second plate.
- 3. The waste energy recovery assembly of Claim 2 wherein said etchings are shaped to induce a swirl into a flow.
- 4. The waste energy recovery assembly of Claim 2 wherein said etchings form a geometric pattern.
- 5. The waste energy recovery assembly of Claim 4 wherein said geometric patterns include an S-shape pattern, a serpentine pattern, a chevron pattern, or a wave-form pattern.

- 6. The waste energy recovery assembly of Claim 1 wherein said first direction is perpendicular to said second direction.
- 7. The waste energy recovery assembly of Claim 1 wherein said supply opening in each of said first plate and said second plate comprises an anode supply opening and a cathode supply opening.
- 8. The waste energy recovery assembly of Claim 7 wherein: said flow channels in said second plate includes anode supply flow channels and cathode supply flow channels;
- said anode supply opening comprises an anode supply opening in and an anode supply opening out positioned for communication with said anode supply flow channels; and

said cathode supply opening comprises a cathode supply opening in and a cathode supply opening out positioned for communication with said cathode supply flow channels.

- 9. The waste energy recovery assembly of Claim 8 wherein said second plate further includes:
- a rib separating said anode supply flow channels from said cathode supply flow channels.
- 10. The waste energy recovery assembly of Claim 1 wherein said first direction is different than said second direction.

5

10

15

11. A method of waste energy recovery, comprising:

communicating an exhaust received at an exhaust opening in a
first plate through exhaust flow channels defined at one side of said first plate to
an exhaust opening out of said first plate, said exhaust flow channels being
orientated in a first direction;

communicating an oxidant received at an anode supply opening in a second plate through anode supply flow channels defined at one side of said second plate to an anode supply opening out of said second plate, said anode supply flow channels being orientated in a second direction, said second plate being disposed in thermal communication with said first plate;

communicating a reformate received at a cathode supply opening in said second plate through cathode supply flow channels defined at said one side of said second plate to an anode supply opening out of said second plate, said cathode supply flow channels being orientated in said second direction; and whereby said oxidant and said reformate are heated.

- 12. The method of Claim 11 wherein said exhaust flow channels are defined by etchings in said first plate, and said anode supply flow channels and said cathode supply flow channels are defined by etchings in said second plate.
- 13. The method of Claim 11 wherein said first direction is different than said second direction.
- 14. The method of Claim 11 wherein said first direction is perpendicular to said second direction.
- 15. The method of Claim 12 further comprising: inducing a swirl into at least one of said exhaust, said oxidant, or said reformate.